



SPECIFICATIONS:

DOORS SHOWN AS FLEXIBLE VINYL IMPACT TRAFFIC DOORS, DOUBLE ACTING, SHALL BE MODEL 300-50 DOORS AS MANUFACTURED BY CHASE INDUSTRIES, INC., CINCINNATI, OHIO, TO FIT DOOR OPENING _____ WIDE BY _____ HIGH.

DOOR TO UTILIZE TOP MOUNTED GRAVITY-OPERATED HINGING SYSTEM, COMPLETE WITH 1/2" THICK ZINC WALL BRACKET WITH BEARINGS AND 5/8" DIAMETER STEEL ROD ARM.
 OPTIONAL 100CRB HINGE

DOOR SHALL BE CONSTRUCTED OF TWO LAYERS OF 2-PLY HEAVY DUTY BELTING (USDA APPROVED) WITH ANTI-ABRASION SURFACE, LAMINATED BACK-TO-BACK. BRACKET POCKET, BALLOON JAMB SEALS, AND TOP AND BOTTOM WIPER SEALS TO BE 45oz. TWO-PLY VINYL COATED NYLON. ALL PERIMETER EDGES TO BE HEAT SEALED TOGETHER.

VISION PANELS TO BE CONSTRUCTED OF .160 CLEAR USDA FLEXIBLE PVC MATERIAL, INSTALLED IN THE CENTER OF THE DOOR PANEL.
 15"x14" - 50 (STANDARD) AT 60" ON CENTER
 22"x22" - 50 (OPTIONAL) AT 64" ON CENTER

MODEL # 300-50, DOUBLE DUTCH AIRGARD BIPARTING FLEXIBLE VINYL IMPACT TRAFFIC DOOR

Chase Doors
 World's Leading Manufacturer Of Traffic Doors
 Cincinnati Ohio, and Redmond Oregon
 Phone Toll Free: 1-800-543-4455

©COPYRIGHT 2000
 CHASE INDUSTRIES, INC.
 SPECIFICATIONS SUBJECT TO
 CHANGE WITHOUT NOTICE.
 1 800-543-4455
 www.chasedoors.com

CUSTOMER INFORMATION:

DATE: 7/27/00 CHASE APPROVAL
 FORM # SD4157 REV.