


OPTIONAL "E" SERIES HINGE



SECTION "AA" OF DOOR

SPECIFICATIONS:

DOOR SHOWN AS SOLID CORE STYLE SERVICE DOOR, DOUBLE ACTING, SHALL BE MODEL SC-3002SSG DOOR AS MANUFACTURED BY CHASE INDUSTRIES, INC., CINCINNATI, OHIO, TO FIT DOOR OPENING _____ WIDE BY _____ HIGH.

DOOR SHALL BE CONSTRUCTED OF 3/4" THICK 7-PLY PLYWOOD CORE WITH 18 GAUGE STAINLESS STEEL FULL HEIGHT, BOTH SIDES. ALL PERIMETER EDGES AND HINGE LOCATIONS TO BE FULLY GASKETED.

COMPLETE WITH CHASE GRAVITY-OPERATED HINGING SYSTEM WITH HARDENED STEEL CAM AND ROLLER. BOTTOM HINGE PIN TO BE 1/2" DIAMETER STEEL MOUNTED TO 3/16" THICK STEEL ANGLE. TOP AND BOTTOM HINGES SHALL MOUNT DIRECTLY THROUGH DOOR BODY.

OPTIONAL "E" SERIES HINGE (NOT GASKETED) SPECIFY RIGHT OR LEFT HAND SWING

ACRYLIC VISION PANEL TO BE 1/4" TH. x 9" x 14" SET IN BLACK RUBBER MOLDING (STD).

INCLUDE OPTIONS AS INDICATED BELOW:

- 3-3/4"x8-3/4" HIGH ALUM. JAMB GUARD
- 3-3/4"x12" HIGH ALUMINUM JAMB GUARD
- 3-3/4"x18" HIGH ALUMINUM JAMB GUARD

NO IMPACT PLATES

BUMPER OPTIONS (BOTH SIDES): YES NO
 STANDARD TEARDROP CROSS-LINKED POLYETHYLENE (SPECIFY COLOR) _____ (AND HEIGHT) _____
 PVC STRIP (SPECIFY COLOR) _____ ALUM. STRIP (SPECIFY LOCATION) _____

MODEL # SC-3002SSG, SINGLE PANEL SOLID CORE STYLE RETAIL SERVICE DOOR

©COPYRIGHT 2000 CHASE INDUSTRIES, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. 1 800-543-4455 www.chasedoors.com

CUSTOMER INFORMATION:

Chase Doors
 World's Leading Manufacturer Of Traffic Doors
 Cincinnati Ohio, and Redmond Oregon
 Phone Toll Free: 1-800-543-4455

DATE: 7/06/00 CHASE APPROVAL

FORM # SD4183

REV.