

SIDE VIEW - 240

SPECIFICATIONS:

DOOR SHOWN AS FLEXIBLE VINYL TRAFFIC DOOR, DOUBLE ACTING, SHALL BE MODEL 240 UNIFLEX DOOR AS MANUFACTURED BY CHASE INDUSTRIES, INC., CINCINNATI, OHIO, TO FIT DOOR OPENING _____ WIDE BY _____ HIGH.

DOOR SHALL BE CONSTRUCTED OF TWO LAYERS OF .117 TEXTURED PVC (USDA APPROVED) WITH ANTI-ABRASION SURFACE, LAMINATED BACK-TO-BACK. BRACKET POCKET AND TOP WIPER SEAL ARE TWO-PLY VINYL COATED NYLON. ALL PERIMETER EDGES AND EDGES OF THE VISION PANEL ARE HEAT SEALED TOGETHER. (SPECIFY COLOR:) FOREST GREEN GRAY CHOCOLATE RED MEDIUM BROWN NAVY ROYAL BLUE BLACK

DOOR TO UTILIZE TOP MOUNTED GRAVITY-OPERATED HINGING SYSTEM, COMPLETE WITH 1/2" THICK ZINC WALL BRACKET WITH BEARINGS AND 5/8" DIAMETER STEEL ROD ARM.


OPTIONAL 100CRB HINGE

VISION PANELS TO BE CONSTRUCTED OF .160 CLEAR USDA FLEXIBLE PVC MATERIAL, INSTALLED IN THE CENTER OF DOOR PANEL.


- 15"x14" - 50 (STANDARD) AT 60" ON CENTER
- 22"x22" - 50 (OPTIONAL) AT 64" ON CENTER

VALANCE OPTION:

WHEN HEIGHT IS LESS THAN 6".
 CONSTRUCTED OF 2-PLY VINYL COATED NYLON ATTACHED TO .080 x 1 x 1 KYDEX ANGLE OF COLOR THAT MATCHES DOOR.
 WHEN HEIGHT IS MORE THAN 6".
 CONSTRUCTED OF 2 LAYERS OF .117 PVC ATTACHED TO 1/8" x 1 x 1 ALUMINUM ANGLE ON BOTH SIDES.



TOP MOUNTED GRAVITY HINGE

MODEL # 240 UNIFLEX, AIRGARD SINGLE PANEL FLEXIBLE VINYL IMPACT TRAFFIC DOOR			
©COPYRIGHT 2000 CHASE INDUSTRIES, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. 1 800-543-4455 www.chasedoors.com	CUSTOMER INFORMATION:		
		DATE: 8/04/00	CHASE APPROVAL
		FORM # SD4090	REV. A