

VP Series

Vinyl-Pro

Roll-Up Door



Pictured: Model VP 4000

- **Separates Environments**
- **Increases Energy Savings**
- **Blocks Dust and Airborne Pollutants**
- **Reduces Noise**
- **Improves Employee Comfort, Security and Productivity**

Features:



Pictured: Model VP 3000

Modular Panels

Innovative design with interchangeable door panels makes TMI's Vinyl-Pro easily convertible to a Screen-Pro or Bird-Pro.

Extruded Aluminum Guide Tracks

Guide the Vinyl-Pro roll-up door smoothly with UHMW[‡] inserts, reducing friction and adding an additional layer of protection and security.

Extruded Aluminum Wind Bars

These high-strength stiffeners combat winds and negative air pressure.

Save-T[®] Breakaway Bar

Prevents Vinyl-Pro doors from breaking if hit. The bottom bar releases in either direction and can easily be put back into the track.

[‡] UHMW: Ultra-High-Molecular-Weight Polyethylene

The Ideal Roll-Up Door For Warehouse-to-Warehouse Separation!

5350 Campbells Run Road • Pittsburgh, PA 15205
1.800.888.9750 • 412.787.9750 • 412.787.3665 (fax)
www.tmi-pvc.com • info@tmi-pvc.com



Vinyl-Pro Roll-Up Doors are available in 18 oz, 22 oz or 40 oz PVC Coated Vinyl with optional clear PVC vision panel.

Popular Vinyl-Pro Colors, Consult Factory for Additional Color Options.



Vinyl-Pro Models:

**VP
1000**

Spring Loaded Manual Roll-Up Door

Maximum Door Size: 10' wide x 10' high
The VP-1000 features a spring-loaded manual movement mechanism with pull down straps.

**VP
2000**

Chain Hoist Manual Roll-Up Door

Maximum Door Size: 14' wide x 14' high
The VP-2000's right side mounted chain hoist is an economical alternative to motorized doors.

**VP
3000**

In-Tube Motorized Roll-Up Door

Maximum Door Size: 14' wide x 14' high
The VP-3000's in-tube motor moves the door at a rate of 12" per second and can be cycled 8 to 10 times per hour. The VP-3000 includes an up/down constant contact rocker switch.

**VP
4000**

External Jackshaft Motorized Roll-Up Door

Maximum Door Size: 14' wide x 14' high
The external jackshaft motor on the VP-4000 moves the door at a rate of 12" to 24" per second and can be cycled 10 to 15 times per hour. The VP-4000 includes a 3 Button Station and Photo Eye.

**VP
5000**

High-Cycle Motorized Roll-Up Door

Maximum Door Size: 14' wide x 14' high
The VP-5000 features a heavy-duty, high-cycle, external jackshaft motor that moves the door at a rate of 12" per second. The VP-5000 includes a 3 Button Station and Photo Eye.

**VP
6000**

Swift Speed Motorized Roll-Up Door

Maximum Door Size: 14' wide x 14' high
The VP-6000 features a heavy-duty, high-cycle, higher speed external jackshaft motor that opens the door at a rate of 36" per second. The VP-6000 includes a 3 Button Station and Photo Eye.

Vinyl-Pro Mounting Styles:

In-Jamb

Requires approximately 8.5" headroom and 4.5" of space on each side of the jamb

Face of Wall

Use when no existing door is present
- can be mounted inside or outside

Inside Stand-Off

Mounts in front of an existing roll-up or sectional door

Options

- Remote Control
- Safety Reversing Edge
- Photo Eye
- Pullcord Station

Options

- NEMA-4 Upgrade
- Safety Reversing Edge
- Pullcord Station
- Remote Control

Options

- NEMA-4 Upgrade
- Safety Reversing Edge
- Pullcord Station
- Remote Control
- Motion Sensors

Options

- NEMA-4 Upgrade
- Safety Reversing Edge
- Pullcord Station
- Remote Control
- Motion Sensors

For Energy Control and Workplace Safety Call TMI at **1.800.888.9750** Today!



5350 Campbells Run Road • Pittsburgh, PA 15205
1.800.888.9750 • 412.787.9750 • 412.787.3665 (fax)
www.tmi-pvc.com • info@tmi-pvc.com

Catalog #
VP1-6000 052013