



TMI INTERNATIONAL, LLC
PHYSICAL PROPERTY DATA SHEET

Product: 60RW Compound Flexible PVC
Description: Aztec Red Weld Screen Flexible PVC Rolls
 .040" to .250" thick
 4" to 60" wide
 Double polished finish

Property	Typical Value	Test Method
Hardness (15 second delay)	83 A Scale	ASTM D2240
Tensile Strength	2800 PSI	ASTM D412
Ultimate Elongation	300%	ASTM D412
100% Modulus	1450 PSI	ASTM D412
Brittleness Temperature	-34° F	ASTM D746
Operating Temperature	0° F to 150° F	
Specific Gravity	1.25	ASTM D792
UV Resistance	Yes	
Flammability	Select material CSFM compliant	

Notes:

Each roll is shipped in a box on a 6" core

The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications, or the results to be obtained there from. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Full-scale testing and product performance are the responsibility of the user. TMI International, LLC shall not be liable; the customer assumes all risk and liability of any use or handling of any material.

SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

REV DATE: 01/22/2016 NST

PENNSYLVANIA
 1.800.888.9750
 5350 Campbells Run Rd
 Pittsburgh, PA 15205

OHIO
 1.866.929.1449
 3333 Win St
 Cuyahoga Falls, OH 44223

GEORGIA
 1.888.606.7325
 4708 S Old Peachtree Rd Ste 700
 Norcross, GA 30071

CALIFORNIA
 1.800.854.7951
 14500 Miller Ave
 Fontana, CA 92336